


Rectifier Diode SXXHN/HR550





Symbol	Characteristics	Conditions	$T_J(^{\circ}\text{C})$	Value	Unit
BLOCKING PARAMETERS					
V_{RRM}	Repetitive peak reverse voltage		160	200-1800	V
I_{RRM}	Repetitive peak reverse current	$V = V_{RRM}$	160	40	mA
CONDUCTING PARAMETERS					
$I_{F(AV)}$	Average on-state current	180 sine, 50Hz, $T_C = 100^{\circ}\text{C}$		550	A
I_{RMS}	RMS on-state current			865	A
I_{FSM}	Non repetitive peak surge on-state current	Sine wave, 10mS without reverse voltage	160	12500	A
I^2t	Permissible surge energy			781	kJ ² S
V_{FM}	Peak on-state voltage drop	On-state current = 1500A	160	1.65	V
V_0	Typical forward conduction Threshold voltage		160	0.85	V
r_0	Typical forward slope resistance		160	0.50	m Ω
THERMAL & MECHANICAL PARAMETERS					
$R_{TH(J-C)}$	Thermal impedance, 180 ^o conduction, Sine	Junction to case		0.072	^o C/W
$R_{TH(C-HK)}$	Thermal impedance	Case to heatsink		0.02	^o C/W
T_J	Maximum Permissible junction temperature			160	^o C
T_{STG}	Storage temperature range			-40 – 160	^o C
F	Mounting Torque			20	NM
W	Weight			875	gms




HIND RECTIFIERS LTD


Rectifier Diode SXXHN/HR550




On State Power Loss




Rectifier Diode SXXHN/HR550




Maximum Permissible Case Temp




Max non repetitive Surge Current







Transient Thermal Impedance Junction to Case



On State Characteristics



Rectifier Diode SXXHN/HR550



Ordering Information: -

S	XX	HN / HR	550
Hirect make Rectifier Diode	$V_{RRM} = XX * 100$ e.g. 12 * 100 = 1200V	HN - Normal Polarity HR - Reverse Polarity	$I_{F(AV)} = 550A$

Hind Rectifiers Ltd reserves the right to change the specifications without notice.

This datasheet specifies technical information for semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.

Hind Rectifiers Ltd
Lake Road
Bhandup (West)
Mumbai – 400 078
Tel: - +91 22 2596 8027/28/29/31
Fax: - +91 22 2596 4114
E-mail: - marketing@hirect.com
Website: - www.hirect.com

June-2008



HIND RECTIFIERS LTD

5 of 5